



Product Code: 07005 (220/240V)
07006 (110/115V)

HT8-1.2 FLOOR SANDER

The world's most popular rental floor sander, a product of modern design and production techniques, provides rental stores with years of high income rentals and an outstanding return on investment.

DESCRIPTION

A high performance drum floor sander designed for the rental and building maintenance markets. A powerful four brush motor drives a dynamically balanced sanding drum which is covered in a unique drum rubber, sanding a high quality finish on all types of wood flooring, decking and many other surfaces. Completely self contained with a high efficiency dust pickup the machine breaks down into three simple component parts for easy transport. With a low voltage trip switch the HT8-1.2 is suitable for use by the professional and homeowner.

USES

The HT8-1.2 Floor Sander will sand all types of wood flooring, including parquet, that require rapid sanding and leveling to a fine score free finish. Also suitable for sanding cork and composition floors.

FEATURES

Simple setup and operation make the HT8-1.2 easy to use and sand a quality finish. The unique drum rubber resists abrasion and damaged caused by exposed nails. While the continuous heavy duty self cooling four brush motor, will not stall or slow down under load when sanding with coarse grit abrasives, removing old surface finishes and deposits of wax and dirt. Simple and speedy service routines keep the HT8-1.2 performing and minimize down time. The drum rubber is easy to replace when needed in just 20 minutes. The high impact ABS injection molded side guards and drum guard will not scar or scuff walls. The drum guard will even support the weight of the machine if the user lifts the sander by the guard. Robust and very strong they withstand the rough handling experienced in rental.



SPECIFICATIONS

Power Supply:	220/250V 110/120V	50/60Hz 50/60Hz
Off Load Current:	220/250V 110/120V	5A 8A
Load Current (Av.):	220/250V 110/120V	8A 15A
Noise:	95dBa at 1 metre	
Vibration:	0.040 M ² H Aeq8 (8 Hr. RMS)	
Switch:	Low voltage trip and overload protection.	
Motor:	Continuous heavy duty AC/DC self cooling four brush.	
Motor RPM:	8,500	
Drum RPM:	3,300	
Drum:	200mm (8") wide extruded aluminium drum dynamically balanced with screw on moulded rubber cover.	
Abrasive:	495mm total length x 203mm wide with notched and angled ends 24 to 120 grit.	
Drive:	Non-slip toothed timing belts and gear cut pulleys.	
Dust Pick-up:	Seated oversize wide blade vacuum fan with adjustable dust pan. Disposable paper dust bags or cloth bag.	
Weight:	41.5kg (91.5lbs)	
Shipping Weight:	50.0kg (110.3lbs)	