



Product Code: 07008 (220/240V)  
07009 (110/115V)

## HTF-2 FLOOR SANDER

A powerful, finely balanced orbital floor sander for sanding and refinishing of all types of wood flooring including pre-finished parquet, plank and laminate flooring systems. Ideal for screen and re-coat of stained floors where the integrity of the stained wood must be maintained

### DESCRIPTION

The HTF-2 is a brand new floor sander from Hiretech®, the leading manufacturer of floor sanders for hire, rental and do-it-yourself users. Superbly engineered to give a swirl free sanding performance the sander glides effortlessly over the floor. The floating handle adjusts to suit the users height making the HTF-2 easy to use and comfortable over long periods of operation. Suitable for use by the professional and homeowner.

### USES

Designed for sanding and refinishing all types of level wood floors in good condition and sanding between coats of varnish where a high standard of final finish is required. The HTF-2 is the ideal floor sander for sanding and refinishing floating parquet and other thin laminated, veneered or solid wood flooring systems including pre-finished. For floors that require buffing before finishing, for example pre-finished where joints between planks and strips are not even, a buffing pad can be used in place of the abrasive screen or sheet.

### FEATURES

Simple operation and safety are major features of the HTF-2. A powerful vacuum system picks-up the fine dust created in orbital sanding which is collected in a disposable paper dust bag for safe handling and disposal. A biased off switch prevents the sander being accidentally left switched on while the handle is easily removed for safe transportation. A integral light provides a flood of illumination in front of sander highlighting the floor surface.



### SPECIFICATIONS

Power Supply:	220/250V	50/60Hz
	110/120V	50/60Hz
Off Load Current:	220/250V	5A
	110/120V	8A
Load Current (Av.):	220/250V	8A
	110/120V	15A
Noise:	95 dBA at 1m	
Vibration:	0.080 M <sup>2</sup> H Aeq8 (8 Hr. RMS )	
Switch:	Bias Off, double pole.	
Motor:	Continuous heavy duty AC/DC self cooling 4 brush.	
Motor RPM:	10,000	
Drive RPM:	3,000	
Sanding Pad:	400mm x 115mm MDF back with nylon hook face.	
Abrasive:	400mm (15.75") x 115mm (4.5") adhesive backed aluminium oxide sheet recommended abrasive range 40 to 180 grit. Abrasive reversible backing pad 240 grit.	
Drive:	Non-slip toothed timing belt with toughened steel pinion and drive gear.	
Dust Pick-up:	Seated oversize vacuum fan, disposable paper dust bags or cloth bag.	
Weight:	43kg (94.8lbs)	
Shipping Weight:	50.0kg (94.8lbs)	