

PRODUCT INFORMATION

HIRETECH[®]

www.hiretech.biz

PFF AQUACOTE GOLD

A superior quality water borne floor lacquer enhanced with natural oils and polyurethane to give a tough, fast drying finish.

DESCRIPTION

A very stable, easy to use lacquer with excellent properties of flexibility and adhesion with good resistance to alcohol, heat and abrasion, it is non-toxic, non hazardous with extremely low odour. Fast drying with full cure reached in just 48 hours AQUACOTE GOLD will not yellow or darken with age unlike traditional oil based finishes.

WHERE TO USE

New and existing wood floors and interior woodwork, ideal for medium to high traffic areas such as halls, stairs and living rooms. Suitable for refinishing most types of factory pre-finished wood and laminate wood floors. Do not use in areas with a high moisture content like bathrooms.

FEATURES

Available in 2.5lt and 5lt packs in gloss and satin finishes. AQUACOTE GOLD can be applied straight from the can. Ideal for floors that must be returned to full use as quickly as possible as full cure is reached in just 48 hours.

FULL APPLICATION INSTRUCTIONS ON REVERSE



SPECIFICATIONS

Type	:	Single component oil based water soluble lacquer in a polyurethane dispersion.
Coverage	:	Hardwood three coats 5m ² /litre. Softwood four coats 3.3m ² /litre.
Resistance to Wear	:	Medium to high.
Resistance to Solvents	:	Medium to high.
Application	:	Brush, lambs wool or synthetic applicator, roller.
Drying Times	:	Surface dry 25 minutes. Hard dry 1 to 2 hours. Light use 6 hours. Fully cured 48 hours.
Cleaning	:	Water.
Flammability	:	Non Flammable
VOC	:	Low (0.3 to 24.99%).
Safety Data Sheet	:	020

PRODUCT CODES

PSTK	Description	Case Qty	Case Weight
15021	Aquacote Gold 2.5lt Gloss	4	12.32kg
15022	Aquacote Gold 5lt Gold	2	11.92kg
15031	Aquacote Gold 2.5lt Satin	4	12.32kg
15032	Aquacote Gold 5lt Satin	2	11.92kg
15131	Floor Finish Brush 10cm	20	2.58kg
15150	Tack Rag	25	0.70kg

Matt finish and 10lt packs available to special order.

IMPORTANT INFORMATION

PFF AQUACOTE GOLD will dry on, and adhere to most types of wood surfaces, however, care must be taken to remove all traces of grease, fats and, polish. ALWAYS test for compatibility before full application. DO NOT apply below an ambient temperature of 8°C. For help and information contact the FLOOR TEAM helpline.

COVERAGE

HARDWOOD : Two coats 5 litres covers approximately 25m²
SOFTWOOD : Three coats 5 litres covers approximately 16.5m²

PREPARATION OF SURFACES

The surface MUST be absolutely clean, dry and free from grease, fats and polish. Old varnish must be lightly sanded using 120 grit or finer sandpaper. If the wood was previously wax polished, clean thoroughly with a lint free cloth and a little white spirit before the final sanding. Allow the white spirit to dry thoroughly then give the wood a final light sanding. Remove all traces of dust by first vacuuming then wiping over with a FLOOR TEAM TACK RAG.

TESTING

Test for compatibility before use. Test coat on a small area with 2 to 3 coats according to appearance required, carefully following the APPLICATION instructions below. If any coat fails to dry properly DO NOT apply to the whole floor or wood surface, contact the FLOOR TEAM helpline for advice. PFF AQUACOTE GOLD is a clear lacquer that will enhance the natural colour and grain of all types of wood. On woods with a high tannin content the natural oils in the PFF may darken on drying. If a natural finish is required on woods with a high tannin content thoroughly seal the wood with a base coat of PFF AQUACOTE.

APPLICATION

Apply in well ventilated conditions, which are dry and warm, not damp or humid. Apply direct from the can using a clean FLOOR TEAM FLOOR FINISH BRUSH or medium weight white bristle brush. Apply liberally and allow the PFF to flow across the surface and find its natural level. Excessive brushing is not necessary, as the PFF will flow easily.

Allow the PFF to dry hard, normally 2 hours and then apply the next coat as required. Lightly sand after the first coat using 180 grit or finer sand paper. Sand between each coat for an exceptionally fine finish or if the time between coats is more than 3 hours. Vacuum and TACK RAG between coats to keep the surface free from dust.

After the last coat has been applied allow the PFF to cure for as long as possible before use - ideally overnight although the floor may be walked on in stocking feet 6 hours after it has dried hard. Avoid placing or moving heavy furniture and objects on the floor or surface, again for as long as possible. Full cure is achieved after 48 hours.

MAINTENANCE

Sweep or vacuum regularly to remove grit and clean using a damp mop. PFF does not need polishing. Scuffmarks may be removed using a non-abrasive cream cleaner.

HEALTH & SAFETY

Keep out of reach of children. Keep container tightly closed. Do not breathe vapour and use only in well ventilated areas. Avoid contact with skin and eyes. Wear suitable gloves and eye protection. Change contaminated clothing.

ENVIRONMENT

Remove as much PFF from brushes and applicators before cleaning. Do not empty into drains or watercourses, or access routes to septic tanks. Local authorities have special facilities for the disposal of waste paints and varnishes. It is recommended that waste PFF be taken to your local household waste disposal site. To avoid the risk of spillage, always store and transport in a secure, upright position.

FIRST AID, FIRE & CLEANING

Eyes: Rinse immediately with plenty of water and seek medical advice if irritation persists. Skin: Wash immediately with soap and plenty of water. If Swallowed: Drink large amounts of water do not induce vomiting, seek medical advice immediately and show this container or label. Fire: In case of fire use water-mist, Co₂, foam or dry powder. Cleaning: To clean brushes use water, allow to dry thoroughly before re-using.

HELPLINE

For help and information on sanding and finishing your floor or other wood surfaces call the FLOOR TEAM helpline in the UK on 01923 332424 or e-mail: floorteam@hiretech.co.uk

Hire Technicians Group Ltd.,
Chalk Hill House, 8 Chalk Hill,
Watford, Hertfordshire WD19 4BH
Tel: 01923 252230 Fax: 01923 238799

MADE IN UK

Floor Team and Hiretech are registered trademarks of Hire Technicians Group Ltd.

Aquacote is a registered trademark of Barfords.

The specifications of the products described in this document are subject to change without prior notice.